




indigoff
glow





Performance

Output ¹	Indirect	Direct
	Watt s/ft Lumens/ft LPW	Watt s/ft Lumens/ft LPW
Low	22.1 W / 1996 lm	22.1 W / 1996 lm
Medium	28.3 W / 2661 lm	28.3 W / 2661 lm
High	33.3 W / 3326 lm	33.3 W / 3326 lm

Ordering Information

1. Fixture ID SPATHA	2. Size 120 cm	3. Color Temperature 27: 2700 K 30: 3000 K 40: 4000 K	4. Output - Direct 4000 K - Indirect 4000 K
5. Voltage UNV: Universal (120/277V)	6. Driver - OF: ON/OFF - DB: Standard 0-10V 1%	7. Sensors / Controls None	8. Mounting - FIL45-WL-BRKT (2) Wall Mounting Brackets - FIL45-SF-CAN Surface Mounted Ceiling Canopy - FIL45-SF-DECO-CAN Deco Surface Mounted Ceiling Canopy - FIL45-EC Endcap - FIL45-SF-PROF-X*IN Custom Length Extrusion; Specify Length in Inches - FIL45-CVR-X*IN Custom Length Painted Cover; Specify Length in inches - FIL45-OP-LENS-X*IN Custom Length Painted Cover; Specify Length in inches
9. Optics None	10. Finish - Felt Enter other color options on page 2. - Felt Height 3 mm / 9 mm / 12 mm	11. Circuit None	12. Options - Anthracite Grey - Black - White - Custom

Specifications

Drivers & Electrical

Remote, dimmable drivers are supplied in enclosures. Several other driver options available; see ordering information. For remote driver box sizes, [click here](#).

Emergency Back-Up

For fixtures three-feet or longer, a 6W emergency driver may be wired to 4ft sections. A 10W driver is also available (consult factory). Emergency circuits for use with building generators are also available.

PoE (Power over Ethernet)

Compatible with virtually all PoE systems including Molex Coresync, Igor, Smartengine, Platformatics, and NuLED SPICEbox. Consult factory for systems not listed. See [here](#) for more info.

Finishes

All luminaires are finished in high quality polyester powder coating. Acoustic material is made of post-consumer recycled PET felt.

Optics

Extruded satin acrylic lenses provide excellent diffusion, high transmission, and no LED imaging.


Construction

Housings are extruded premium, recycled aluminum. Individual fixtures are available up to 12' long and may be specified as nominal or precision lengths. Precision lengths are supplied within 1/8" tolerance.

Joined Runs


Runs of any length may be specified and are comprised of multiple, factory-engineered, joined sections. Individually specified luminaires are not field joinable.

Optics




Representative distribution and peak candela.


Mounting
Options



Aircraft cable
5" canopy



Aircraft cable
3.5" canopy




Pendant stem

Refer to factory shop drawings for all suspension points. Any modification of factory-designated suspension locations may result in damage to the fixtures and is strictly prohibited. Do not proceed with installation unless the instructions are fully understood."

Felt
Colors



RED



CHERRY




ORANGE



CITRUS



GREEN



FOREST GREEN



DEEP BLUE




BLACK



OXFORD



SOFT GREY



NAVY BLUE



BLUE



MOKA



IVORY



PEACH



TEAL



WHITE



VIOLET